



MATERIAL SAFETY DATA SHEET

HMIS Ratings	
Health	2
Flammability	3
Reactivity	0
Protection	X

Chemical Product and Company Identification

Manufacturer Information Blue Ribbon Products, Inc.
7687 Winton Drive, Bldg. 130
Indianapolis, IN 46268

Phone (317) 972-7970 * (888) 274-2266

Emergency Phone CHEMTREC
1-800-424-9300
FOR INTERNATIONAL CALLS
(703) 527-3887

Date Modified 4/25/05

Supercedes

Product Identity Adhesive Label Remover II VOC

Product Use Automotive Reconditioning Product

Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt.%	PEL-OSHA	Exposure Limits		Carcinogen
				TLV-ACGIH		
BENZENE, DIMETHYL-	1330-20-7	10-30	100 ppm 435 mg/m3	100 ppm	No	
NAPHTHA, PETROLEUM, Non-hazardous and other	64742-89-8	10-30	300 ppm	300 ppm	No	
Ingredients below reportable levels	Proprietary	60	N/AP	N/AP	N/AP	

Hazards Identification

Potential Health Effects

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eyes This product may cause irritation to the eyes.

Inhalation This product may cause irritation to the respiratory system. Excessive inhalation of this product may cause headache, dizziness, blurred vision, nausea and vomiting.

Ingestion Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazard Statements
FLAMMABLE

CAUTION: EYE AND SKIN IRRITANT.

First Aid Measures

First Aid

Skin	For skin contact, wash immediately with soap and water. Immediately take off all contaminated clothing. Wash contaminated clothing before reuse. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	If inhaled, immediately remove the affected person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen.
Ingestion	If the material is swallowed, get immediate medical attention or advice – Do not induce vomiting.
Notes to Physician	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide and carbon dioxide.

Extinguishing Media

Dry chemical, alcohol foam, carbon dioxide.

General Fire Hazards

DANGEROUS when exposed to heat or flame. This material can be ignited by flame or spark under all normal atmospheric conditions.

Fire fighting Equipment/Instructions

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Flash Point 50° F lowest flashing component

Flammability Limits in Air, Lower, % by Volume 0.98%

Flammability Limits in Air, Upper, % by Volume 5%

Accidental Release Measures

Containment Procedures

Remove sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps.

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

Handling and Storage

Handling Procedures

Keep this product from heat, sparks, or open flame.

Storage Procedures

Keep the container tightly closed and in a cool, well ventilated place. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit (48C). Eliminate all sources of ignition.

Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves. Use of impervious boots is recommended. Use of an impervious apron is recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good hygiene practices when handling this material, including changing and laundering work clothes after use. Discard contaminated shoes and leather goods. Eye wash fountain and emergency showers are recommended.

Physical & Chemical Properties

Specific Gravity	0.8
Vapor Pressure	<20 mm/Hg
Vapor Density	>1
Solubility (H₂O)	Insoluble

Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material.

Hazardous Decomposition

Upon decomposition, this product may yield oxides of nitrogen and ammonia, carbon dioxide, carbon monoxide and other low molecular weight hydrocarbons.

Hazardous Polymerization

Will not occur.

Incompatibility

This product may react with strong oxidizing agents.

Toxicological Information

Toxicological Information

No data available for this product.

Ecological Information

Ecological Information

No data available for this product.

Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Transportation Information

US DOT HMR INFORMATION

Proper Shipping Name	Flammable liquids, nos (Petroleum Distillates, Xylene)		
Identification Number	UN1993	Packaging Group	II
Hazard Class	3		

Regulatory Information

US FEDERAL REGULATIONS

CERCLA/SARA – Section 313 – Emission reporting
BENZENE, DIMETHYL-

Other Information

Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Prepared By Technical Department

Issue Date 1/16/2008