

MATERIAL SAFETY DATA SHEET

HOU-CHEMICAL DIVISION
M.B.E.A.D.S. INC.
201 EAST HARRISON ST.
MICHIGAN CITY, IN 46360



EMERGENCY # 1-800-345-2430
FAX # 1-219-874-9795

2/1/2000

SECTION I – PRODUCT INFORMATION

PRODUCT NAME:SNAP WAX

PRODUCT USE:AUTO WAX

HMIS RATING

HEALTH

2

FLAMMABILITY

4

REACTIVITY

PERSONAL PROTECTION

SECTION II – HAZARDOUS INGREDIENT INFORMATION (29 CFR 1910.1200)

CHEMICAL NAME	CAS NUMBER	%	EXPOSURE LIMITS
PETROLEUM DISTILLATES	64742-47-8	5-10	500 PEL
KAOLIN CLAY	66402-68-4	5-10	5MG/M3

SECTION III- PHYSICAL AND CHEMICAL DATA

PHYSICAL STATE: LIQUID

APPEARANCE:WHITE EMULSION

ODOR:SOLVENT ODOR

PH:7

EVAPORATION RATE (WATER=1)

BOILING POINT:212F

VAPOR DENSITY (AIR = 1)

VAPOR PRESSURE:

SPECIFIC GRAVITY:.85

SOLUBILITY IN WATER:MISCIBLE

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

FLASH POINT AND METHOD: 67F PMCC

FLAMMABLE LIMITS:NOT ESTABLISHED

EXTINGUISHING MEDIA:DRY CHEMICAL,CO2

SPECIAL FIRE FIGHTING PROCEDURES:

UNUSAL FIRE AND EXPLOSION HAZARDS:

SECTION V – REACTIVITY HAZARD DATA

STABILITY:STABLE

INCOMPATIBILITY(MATERIALS TO AVOID)NONE KNOWN

HAZARDOUS DECOMPOSITION PRODUCTS:

HAZARDOUS POLYMERIZATION:WILL NOT OCCUR

SECTION VI – CONTROL AND PROTECTIVE MEASURES

GLOVES: THE USE OF RUBBER GLOVES IS RECOMMENDED.

SAFETY GLASSES: THE USE OF SAFETY GLASSES IS RECOMMENDED.

RESPIRATORY: NOT APPLICABLE

VENTILATION: ADEQUATE.