



MATERIAL SAFETY DATA SHEET

HMIS Ratings	
Health	2
Flammability	2
Reactivity	0
Protection	X

Chemical Product and Company Identification

Manufacturer Information Blue Ribbon Products, Inc.
7687 Winton Drive, Bldg. 130
Indianapolis, IN 46268

Phone (317) 972-7970 * (888) 274-2266

Emergency Phone CHEMTREC
1-800-424-9300
FOR INTERNATIONAL CALLS
(703) 527-3887

Date Modified 10/01/04

Product Identity Haze Away 1 Smooth Compound

Product Use Automotive Reconditioning Product

Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt.%	PEL-OSHA	Exposure Limits		Carcinogen
				TLV-ACGIH		
MINERAL SPIRITS	8052-41-3	30 – 60	100 ppm TWA; 525 mg/m3 TWA	100 ppm TWA	No	
KAOLIN	66402-68-4	1 – 5			No	
AMORPHOUS SILICA	61790-53-2	1 – 5	6 mg/m3 TWA	10 mg/m3 TWA Inhalable fraction; 3 mg/m3 TWA respirable fraction the value is for total dust containing no asbestos and < 1% free silica	No	
Non-hazardous and other Ingredients below reportable levels.	Proprietary	49	N/AP	N/AP	N/AP	

Hazards Identification

Potential Health Effects

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eyes	This product may be severely irritating to the eyes. Symptoms including itching, burning, redness and tearing.
Inhalation	This product may cause irritation to the respiratory system.
Ingestion	Ingestion of this product may cause nausea, vomiting and diarrhea.

First Aid Measures

First Aid Skin	Immediately take off all contaminated clothing. For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen.
Ingestion	If the material is swallowed, get immediate medical attention or advice – Do not induce vomiting.

Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Carbon dioxide. Alcohol foam.

General Fire Hazards

This product is combustible at high temperatures. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

Flash Point 110° F

Flammability Limits in Air, Lower, % by Volume 0.7%

Flammability Limits in Air, Upper, % by Volume 6%

Accidental Release Measures

Containment Procedures

Eliminate sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

Handling and Storage

Handling Procedures

Avoid prolonged or repeated skin contact with this material. Keep this product from heat, sparks, or open flame.

Storage Procedures

Keep the container tightly closed and in a cool, well-ventilated place. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit. Do not freeze.

Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves. Use of impervious apron and boots are recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good industrial hygiene practices in handling this material. Eye wash fountain and emergency showers are recommended.

Physical & Chemical Properties

Boiling Point	> 212 F
Specific Gravity	> 1
Vapor Pressure	< 20 mm/Hg
Evaporation Rate	Faster than water
Vapor Density	> 1
Solubility (H₂O)	dispersible
pH	8.5
Freezing Point	32 F

Chemical Stability & Reactivity Information

Chemical Stability

Stable under normal conditions.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

Strong oxidizing agents (peroxides, chlorine, strong acids).

Toxicological Information

Toxicological Information

No data available for this product.

Ecological Information

Ecological Information

No data available for this product.

Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Transportation Information

US DOT HMR Information

Proper Shipping Name	Flammable Liquids, N.O.S. (Petroleum Distillates)
Identification Number	UN1993
Packaging Group	III
Hazard Class	3

Regulatory Information

US Federal Regulations

Other Information

Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Prepared By Technical Department
Issue Date 1/17/2008