

MATERIAL SAFETY DATA SHEET

HOU-CHEMICAL DIVISON
M.B.E.A.D.S. INC.
201 EAST HARRISON ST.
MICHIGAN CITY, IN 46360



EMERGENCY # 1-800-345-2430
FAX # 1-219-874-9795

REVISED 12/31/98

SECTION I – PRODUCT INFORMATION

PRODUCT NAME: CLEAR GLOSS DRESSING

PRODUCT USE: TIRE AND VINYL DRESSING

HMIS RATING

HEALTH

1

FLAMMABILITY

2

REACTIVITY

PERSONAL PROTECTION

SECTION II – HAZARDOUS INGREDIENT INFORMATION (29 CFR 1910.1200)

CHEMICAL NAME	CAS NUMBER	%	EXPOSURE LIMITS
ALKYLATION NAPHTHA, HEAVY	63148-62-9	15-20	100PPM TWA
PETROLEUM DISTILLATES	64741-65-7	75-80	100 PPM TWA

SECTION III – PHYSICAL AND CHEMICAL DATA

PHYSICAL STATE: LIQUID

ODOR: STRAWBERRY SCENT

EVAPORATION RATE (WATER=1): 1.17

VAPOR DENSITY (AIR = 1): 4.0

SPECIFIC GRAVITY: .77

APPEARANCE: CLEAR

PH:

BOILING POINT: 346 F

VAPOR PRESSURE: 1.2

SOLUBILITY IN WATER:

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT AND METHOD: 125F TCC

EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, HALON

SPECIAL FIRE FIGHTING PROCEDURES:

UNUSUAL FIRE AND EXPLOSION HAZARDS:

FLAMMABLE LIMITS: LEL 1.0, UEL 6.0

SECTION V – REACTIVITY HAZARD DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG ACIDS,
BASES OR SELECTED AMINES.

HAZARDOUS DECOMPOSITION PRODUCTS:

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – CONTROL AND PROTECTIVE MEASURES

GLOVES: THE USE OF RUBBER GLOVES IS RECOMMENDED.

SAFETY GLASSES: THE USE OF SAFETY GLASSES IS RECOMMENDED.

RESPIRATORY: NOT APPLICABLE

VENTILATION: ADEQUATE.