MATERIAL SAFETY DATA SHEET

HOU-CHEMICAL DIVISON
M.B.E.A.D.S. INC.
201 EAST HARRISON ST.
MICHIGAN CITY, IN 46360

FIRST HOU-1-Chem in AUTOMOTIVE CHEMICAL PRODUCTS

EMERGENCY # 1-800-345-2430
FAX # 1-219-874-9795
CHENTREC # 1-800-424-9300

REVISED 9/22/2000

SECTION I –PRODUCT INFORMATION

PRODUCT NAME:PAINT SEALANT AND RENEWER
PRODUCT USE:AUTOMOTIVE PAINT SEALANT

HMIS RATING **HEALTH** 1 **FLAMMABILITY** 2 **REACTIVITY** ☐ **PERSONAL PROTECTION** ☐

SECTION I I – HAZARDOUS INDREDIENT INFORMATION (29 CFR 1910.1200)

CHEMICAL NAME	CAS NUMBER	%	EXPOSURE LIMITS OSHA PEL	ACGIH TLV
PETROLEUM DISTILLATES	64742-47-8	5-10	500	
	64742-88-7	5-10	500	

SECTION I I I- PHYSICAL AND CHEMICAL DATA

PHYSICAL STATE: LIQUID
APPEARANCE: WHITE THICK LIQUID
ODOR:SLIGHT SOLVENT ODOR
PH:N/A
EVAPORATION RATE (WATER=1)
BOILING POINT:
VAPOR DENSITY (AIR = 1)
VAPOR PRESSURE:
SPECIFIC GRAVITY:1.0
SOLUBILITY IN WATER:MISCIBLE

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

FLASH POINT AND METHOD:107 F PMCC
FLAMMABLE LIMITS:N/A
EXTINGUISHING MEDIA:CO 2 DRY CHEMICAL
SPECIAL FIRE FIGHTING PROCEDURES:
UNUSAL FIRE AND EXPLOSION HAZARDS:N/A

SECTION V – REACTIVITY HAZARD DATA

STABILITY:STABLE **INCOMPATIBILITY(MATERIALS TO AVOID)**
HAZARDOUS DECOMPOSTION PRODUCTS:
HAZARDOUS POLYMERIZATION:WILL NOT OCCUR.

SECTION VI – CONTROL AND PROTECTIVE MEASURES

GLOVES: **THE USE OF RUBBER GLOVES IS RECOMMENDED.**
SAFETY GLASSES: **THE USE OF SAFETY GLASSES IS RECOMMENED.**
RESPIRATORY: **NOT APPLICABLE**
VENTILATION: **ADEQUATE.**