

MATERIAL SAFETY DATA SHEET

HOU-CHEMICAL DIVISION
M.B.E.A.D.S. INC.
201 EAST HARRISON ST.
MICHIGAN CITY, IN 46360



EMERGENCY # 1-800-345-2430
FAX # 1-219-874-9795

REVISED 9/26/2000

SECTION I – PRODUCT INFORMATION

PRODUCT NAME: TAR, WAX AND GUM REMOVER

PRODUCT USE:

HMIS RATING

HEALTH

2

FLAMMABILITY

4

REACTIVITY

PERSONAL PROTECTION

SECTION II – HAZARDOUS INGREDIENT INFORMATION (29 CFR 1910.1200)

CHEMICAL NAME	CAS NUMBER	%	EXPOSURE LIMITS	
			OSHA PEL	ACGIH TLV
PETROLEUM DISTILLATES	64742-47-8	20-30	500	
PETROLEUM DISTILLATES	64742-89-8	20-30	300	
AROMATIC HYDROCARBONS	1330-20-7	15-25	100	
CHLORINATED HYDROCARBON	127-18-4	25-30	100	

SECTION III - PHYSICAL AND CHEMICAL DATA

PHYSICAL STATE: LIQUID

ODOR: SOLVENT SCENT

EVAPORATION RATE (WATER=1)

VAPOR DENSITY (AIR = 1)

SPECIFIC GRAVITY: 1.10

APPEARANCE: CLEAR LIQUID

PH:

BOILING POINT: 250 F

VAPOR PRESSURE:

SOLUBILITY IN WATER:

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT AND METHOD: 67 F PMCC

EXTINGUISHING MEDIA: CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: FLAMMABLE LIQUID

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLAMMABLE LIQUID

FLAMMABLE LIMITS:

SECTION V – REACTIVITY HAZARD DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID)

HAZARDOUS DECOMPOSITION PRODUCTS:

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – CONTROL AND PROTECTIVE MEASURES

GLOVES: THE USE OF RUBBER GLOVES IS RECOMMENDED.

SAFETY GLASSES: THE USE OF SAFETY GLASSES IS RECOMMENDED.

RESPIRATORY: NOT APPLICABLE

VENTILATION: ADEQUATE.