



# MATERIAL SAFETY DATA SHEET

## Chemical Product and Company Identification

**Manufacturer Information** Blue Ribbon Products, Inc.  
7687 Winton Drive, Bldg. 130  
Indianapolis, IN 46268

**Phone** (317) 972-7970 \* (888) 274-2266

**Emergency Phone** CHEMTREC  
1-800-424-9300  
FOR INTERNATIONAL CALLS  
(703) 527-3887

**Date Modified** 4/22/04

**Product Identity** No. 88 Super Rubbing compound 900 Gram

**Product Use** Automotive Reconditioning Product

**Version #** 1.0

**CAS#** Mixture

## Composition / Information on Ingredients

<u>Ingredient Name</u>	<u>CAS Number</u>	<u>Wgt.%</u>	<u>Risk Codes</u>
KEROSINE, PETROLEUM	8008-20-6	10 – 30	R65
SILICA, CRYSTALLINE	14808-60-7	10 – 30	R37
AMMONIA	7664-41-7	0.5 – 1.5	R34
Non-hazardous and other ingredients below reportable levels.	Proprietary	59	N/AP

## Hazards Identification

**Hazard Statements**  
Combustible

## First Aid Measures

### First Aid

<b>Skin</b>	Immediately take off all contaminated clothing. For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.
<b>Eyes</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
<b>Inhalation</b>	If not breathing, give artificial respiration, preferably mouth –to –mouth. If breathing is difficult, give oxygen.
<b>Ingestion</b>	If the material is swallowed, get immediate medical attention or advice – Do not induce vomiting.

## Fire Fighting Measures

### Hazardous Combustion Products

Carbon monoxide and carbon dioxide and other hydrocarbon fragments.

### Extinguishing Media

Carbon dioxide. Alcohol foam.

### General Fire Hazards

This product is combustible at high temperatures. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.

### Fire fighting Equipment/Instructions

Firefighters should wear protective clothing and self contained breathing apparatus.

<b>Flash Point</b>	125 F (51.7 C) lowest flashing component
<b>Flammability Limits in Air, Lower, % by Volume</b>	.07%

## Accidental Release Measures

### Containment Procedures

Eliminate sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

### Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

## Handling and Storage

### Handling Procedures

Avoid prolonged or repeated skin contact with this material. Keep this product from heat, sparks, or open flame.

### Storage Procedures

Keep the container tightly closed and in a cool, well – ventilated place. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit (48 C). Do not freeze.

## Exposure Controls / Personal Protection

### Engineering Controls

Explosion proof exhaust ventilation should be used.

### Personal Protective Equipment

#### Eyes/Face

Wear chemical goggles.

#### Skin

Use impervious gloves. Use of impervious apron and boots are recommended.

#### Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

#### General

Use good industrial hygiene practices in handling this material. Eye wash fountain and emergency showers are recommended.

## Physical & Chemical Properties

<b>Boiling Point</b>	212 F
<b>Specific Gravity</b>	1
<b>Vapor Pressure</b>	< 20 mm/Hg
<b>Evaporation Rate</b>	> 1-Butyl Acetate = 1
<b>Vapor Density</b>	> 1
<b>Solubility (H<sub>2</sub>O)</b>	Dispersible
<b>pH</b>	8.5
<b>Freezing Point</b>	32 F

## Chemical Stability & Reactivity Information

### Chemical Stability

Stable under normal conditions.

### Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

### Hazardous Polymerization

Will not occur.

### Incompatibility

Strong oxidizing agents. (peroxides, chlorine, strong acids).

## Toxicological Information

### Toxicological Information

No data available for this product.

## Potential Health Effects

Skin	Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.
Eyes	This product may be severely irritating to the eyes. Symptoms include itching, burning, redness and tearing.
Inhalation	This product may cause irritation to the respiratory system.
Ingestion	Ingestion of this product may cause nausea, vomiting, and diarrhea.

## Ecological Information

### Ecological Information

No data available for this product.

## Disposal Considerations

### Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

## Transportation Information

### General

This product is not regulated as a hazardous material by the United States(DOT) or Canadian (TDG) transportation Regulations.

### European Ground Transport (ADR/RID Requirements)

<b>Proper shipping Name</b>	Flammable Liquids, nos, (Kerosene,
<b>UN Number</b>	UN1993
<b>Class /Division</b>	3
<b>Packing Group</b>	III

### Maritime Transport (IMDG Requirements)

<b>Proper Shipping Name</b>	Flammable Liquids, nos, (Kerosene,)
<b>UN Number</b>	UN1993
<b>Class /Division</b>	3
<b>Packing Group</b>	III

## Regulatory Information Labeling Information

**Harmful (XN)** **Flammable**

### Risk Codes and Phrases

R10 Flammable  
R65 Harmful: may cause lung damage if swallowed

### Safety Codes and Phrases

S24/25 Avoid contact with skin and eyes.  
S16 Keep away from sources of ignition – no smoking

## Other Information

### Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

**Prepared By**                      Technical Department

**Issue Date**                        1/17/2008